

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Manta #207 Modified Adhesive : :
 Product code : Manta-207
 Formula : Manta-207

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Roofing/Waterproofing

1.3. Details of the supplier of the safety data sheet

Manta Roofing Products
 1200 SE 20th street
 FT. LAUDERDALE, FL 33316 - UNITED STATES
 T 954-330-4901
www.mantarroof.com

1.4. Emergency telephone number

Emergency number : 800-424-9300
 Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3	H226
Muta. 1B	H340
Carc. 1B	H350
STOT RE 1	H372

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

0

Hazard pictograms (GHS-US) :



GHS02



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

- H226 - Flammable liquid and vapour
- H340 - May cause genetic defects (Dermal, Inhalation)
- H350 - May cause cancer (Inhalation, Dermal)
- H372 - Causes damage to organs (central nervous system, eye, Skin, lung, liver) through prolonged or repeated exposure (Dermal, Inhalation)

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from open flames. - No smoking
- P233 - Keep container tightly closed
- P240 - Ground/bond container and receiving equipment
- P241 - Use explosion-proof electrical/ventilating/lighting/... equipment
- P242 - Use only non-sparking tools
- P243 - Take precautionary measures against static discharge
- P260 - Do not breathe fume, gas, vapours
- P264 - Wash hands thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P280 - Wear protective gloves, protective clothing
- P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P308+P313 - If exposed or concerned: Get medical advice/attention

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P314 - Get medical advice/attention if you feel unwell
P370+P378 - In case of fire: Use carbon dioxide (CO₂), foam, dry extinguishing powder to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
asphaltic bitumen, not cut back	(CAS No) 8052-42-4	60 - 80	Not classified
kaolin	(CAS No) 1332-58-7	15 - 30	Not classified
Stoddard solvent	(CAS No) 8052-41-3	20 - 25	Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
attapulgit	(CAS No) 12174-11-7	5 - 10	Carc. 2, H351
cellulose	(CAS No) 9004-34-6	3 - 7	Not classified

Full text of H-phrases: see section 16 *The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : There are potential chronic health effects to consider.
Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.
Symptoms/injuries after skin contact : May cause an allergic skin reaction. May cause moderate irritation.
Symptoms/injuries after eye contact : Eye irritation.
Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapour-air mixture.

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reactivity : Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage. Isolate from fire, if possible, without unnecessary risk. No flames, no sparks. Eliminate all sources of ignition. Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Gloves.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Do not breathe fume, spray, vapours.

Handling temperature : < 110 (≤ 100) °F

Hygiene measures : Do not eat, drink or smoke when using this product. Wash Always wash hands after handling the product, Do not eat, drink or smoke when using this product, Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition.

Storage temperature : < 43 °C

Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: ignition sources.

Prohibitions on mixed storage : No data available.

Storage area : Meet the legal requirements.

Special rules on packaging : Keep only in original container. meet the legal requirements. Store in a closed container. correctly labelled.

Packaging materials : No data available.

7.3. Specific end use(s) No

additional information available

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Manta #207 Modified Adhesive	
ACGIH	Not applicable
OSHA	Not applicable
asphaltic bitumen, not cut back (8052-42-4)	
OSHA	Not applicable
attapulgate (12174-11-7)	
ACGIH	Not applicable
OSHA	Not applicable
cellulose (9004-34-6)	
OSHA	Not applicable
kaolin (1332-58-7)	
OSHA	Not applicable

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Materials for protective clothing	: PICM010.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: BLACK FIBERED MASTIC.
Colour	: Black
Odour	: Petroleum-like odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 300 (≤ 450) °F
Flash point	: 106 °F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.293 kPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: 1.02 - 1.12
Density	: 8 - 9
Percent Solids	: > 75 %

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Water: 0 % Acetone: ≈ g/100ml Organic solvent:≈ 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available

9.2. Other information

VOC content : < 250 (≤ 250) g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Lack of data)

asphaltic bitumen, not cut back (8052-42-4)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
cellulose (9004-34-6)	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 6 mg/l/4h (Rat)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : May cause genetic defects (Dermal, Inhalation).
Carcinogenicity : May cause cancer (Inhalation, Dermal).

asphaltic bitumen, not cut back (8052-42-4)	
IARC group	3 - Not classifiable
attapulгите (12174-11-7)	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable

--	--

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (central nervous system, eye, Skin, lung, liver) through prolonged or repeated exposure (Dermal, Inhalation).
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction. May cause moderate irritation.
Symptoms/injuries after eye contact	: Eye irritation.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:

SECTION 12: Ecological information

12.1. Toxicity

asphaltic bitumen, not cut back (8052-42-4)	
LC50 fish 1	> 1000 mg/l (96 h; Pisces)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)

cellulose (9004-34-6)	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)

12.2. Persistence and degradability

Manta #207 Modified Adhesive	
Persistence and degradability	Not established.

asphaltic bitumen, not cut back (8052-42-4)	
Persistence and degradability	Not readily biodegradable in water.

attapulгите (12174-11-7)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

cellulose (9004-34-6)	
Persistence and degradability	Biodegradable in water.

kaolin (1332-58-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Manta #207 Modified Adhesive	
Bioaccumulative potential	Not established.

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

asphaltic bitumen, not cut back (8052-42-4)	
Log Pow	> 6 (Calculated)
Bioaccumulative potential	Not bioaccumulative.
attapulgite (12174-11-7)	
Bioaccumulative potential	No bioaccumulation data available.
cellulose (9004-34-6)	
Bioaccumulative potential	Bioaccumulation: not applicable.
kaolin (1332-58-7)	
Bioaccumulative potential	No bioaccumulation data available.
Stoddard solvent (8052-41-3)	
Log Pow	3.16-7.06

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer :
Effect on the global warming : No known ecological damage caused by this product.
Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations.
Additional information : Industrial waste.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Transport document description : Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated, III
UN-No.(DOT) : Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated
Packing group (DOT) : III - Minor Danger

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Manta #207 Modified Adhesive
Not listed on the United States SARA Section 313
asphaltic bitumen, not cut back (8052-42-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

attapulgite (12174-11-7)
Not listed on the United States TSCA (Toxic Substances Control Act) inventory
cellulose (9004-34-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
kaolin (1332-58-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Stoddard solvent (8052-41-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

Manta #207 Modified Adhesive	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

attapulgite (12174-11-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

asphaltic bitumen, not cut back (8052-42-4)
U.S. - New Jersey - Right to Know Hazardous Substance List

cellulose (9004-34-6)
U.S. - New Jersey - Right to Know Hazardous Substance List

kaolin (1332-58-7)
U.S. - New Jersey - Right to Know Hazardous Substance List

Stoddard solvent (8052-41-3)
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.

Manta #207 Modified Adhesive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 2 Moderate Hazard
Physical : 0 Minimal Hazard
Personal Protection : p

ZLF-PMS 364 CUSTOM TEMPLATE

All information contained in this MSDS is based on current technical data believed to be accurate and reliable. Additions of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since these conditions are outside our control, we furnish this MSDS without any express or implied warranties.